






















RFID for Apparel

Item	Product Name	Chip	EPC&User	TID	Antenna Size (L*W)	Antenna Shape	Read Range (Tagformance, 4W))	Delivery Format	Applications
1	OS1222-U8	UCODE 8 UCODE 9xe	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	12*22.5mm		865MHZ: 2m 920MHZ: 5m	Dry inlay Wet inlay Label	Apparel Retail
	OS1222-U9	UCODE 9	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number					
2	OS4015-U8	UCODE 8 UCODE 9xe	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	15*40mm		865MHZ: 5m 920MHZ: 9m	Dry inlay Wet inlay Label	Apparel Retail
	OS4015-U9	UCODE 9	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number					
3	OS1642-U8	UCODE 8 UCODE 9xe	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	16*42mm		865MHZ: 6.5m 920MHZ: 9m	Dry inlay Wet inlay Label	Apparel Retail
	OS1642-U9	UCODE 9	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number					
4	OS1570-U8	UCODE 8 UCODE 9xe	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	15*70mm		865MHZ: 8m 920MHZ: 17m	Dry inlay Wet inlay Label	Apparel
	OS1570-U9	UCODE 9	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number					
5	OS1470-U8	UCODE 8 UCODE 9xe	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	14*70mm		865MHZ: 10m 920MHZ: 20m	Dry inlay Wet inlay Label	Apparel
	OS1470-U9	UCODE 9	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number					
6	OS3050-U8	UCODE 8 UCODE 9xe	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	30*50mm		865MHZ: 13m 920MHZ: 15m	Dry inlay Wet inlay Label	Apparel
	OS3050-U9	UCODE 9	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number					
7	OS5030-U8	UCODE 8 UCODE 9xe	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	50*30		865MHZ: 11.5m 920MHZ: 16m	Dry inlay Wet inlay Label	Apparel
	OS5030-U9	UCODE 9	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number					
8	OS1470-F0051E	FM13UF0051E	EPC: 128-bit User: 32-bit	96-bit / 48-bit unique serial number	14*70mm		865MHZ:7.5m 920MHZ:18m	Dry inlay Wet inlay Label	Apparel Retail
	OS1470-F0011E	FM13UF011E	EPC: 96-496-bit User: 112-512-bit	96-bit / 48-bit unique serial number					
9	OS3050-F0051E	FM13UF0051E	EPC: 128-bit User: 32-bit	96-bit / 48-bit unique serial number	30*50mm		865MHZ:5m 920MHZ:16m	Dry inlay Wet inlay Label	Apparel Retail
	OS3050-F0011E	FM13UF011E	EPC: 96-496-bit User: 112-512-bit	96-bit / 48-bit unique serial number					

	Product Name	Chip	EPC&User	TID	Antenna Size (L*W)	Antenna Shape	Read Range (Tagformance, 4W)	Delivery Format	Applications
10	OS1222-R6	MR6	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number	12.5*22mm		865MHZ: 1m 920MHZ: 3m	Dry inlay Wet inlay Label	Apparel Retail Jewelry
	OS1222-R6P	MR6-P	EPC: 128-bit User: 32-bit	96-bit / 48-bit unique serial number					
11	OS4015-R6	MR6	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number	15*40mm		865MHZ: 3m 920MHZ: 6.8m	Dry inlay Wet inlay Label	Apparel Retail
	OS4015-R6P	MR6-P	EPC: 128-bit User: 32-bit	96-bit / 48-bit unique serial number					
12	OS5030-R6	MR6	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number	50*30mm		865MHZ: 4m 920MHZ: 11m	Dry inlay Wet inlay Label	Apparel
	OS5030-R6P	MR6-P	EPC: 128-bit User: 32-bit	96-bit / 48-bit unique serial number					
13	OS7015-R6	MR6	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number	70*15mm		865MHZ: 2.6m 920MHZ: 9m	Dry inlay Wet inlay Label	Apparel
	OS7015-R6P	MR6-P	EPC: 128-bit User: 32-bit	96-bit / 48-bit unique serial number					
14	A61F-MR6	MR6	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number	15*40mm		6m	Dry inlay Wet inlay Label	Apparel Retail
	A61F-MR6-P	MR6-P	EPC: 128-bit User: 32-bit	96-bit / 48-bit unique serial number					
15	OS1570-R6-FZ	MR6	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number	15*70mm		865MHZ: 10m 920MHZ: 12m	Dry inlay Wet inlay Label	Apparel
	OS1570-R6P-FZ	MR6-P	EPC: 128-bit User: 32-bit	96-bit / 48-bit unique serial number					
16	OS1470-H10	Alien H10	EPC: 128(96)-bit User: 0(32)-bit	96-bit / 48-bit unique serial number	14*70mm		865MHZ: 7m 920MHZ: 12.5m	Dry inlay Wet inlay Label	Apparel Retail
17	OS3050-H10	Alien H10	EPC: 128(96)-bit User: 0(32)-bit	96-bit / 48-bit unique serial number	30*50mm		865MHZ: 4m 920MHZ: 12m	Dry inlay Wet inlay Label	Apparel Retail
	OS1642-H10	Alien H10	EPC: 128(96)-bit User: 0(32)-bit	96-bit / 48-bit unique serial number	16*42mm		865MHZ: 3.5m 920MHZ: 9m	Dry inlay Wet inlay Label	Apparel Retail
18	100x50mm UHF Woven Label	UCODE 8	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	40*15mm		865MHZ: 5m 920MHZ: 9m	Label	Apparel Retail
	80x30mm UHF Woven Label	UCODE 9	EPC: 96-bit User: N/A	96-bit / 48-bit unique serial number	70*14mm		865MHZ: 10m 920MHZ: 20m	Label	Apparel

19	70*15mm UHF Laundry Label	UCODE 8	EPC: 128-bit User: N/A	96-bit / 48-bit unique serial number	70*15mm		865MHZ: 8m 920MHz: 17m	Label	Industrial washing
<p>1. All antenna shapes can be customized to wet inlays/labels/woven label/hang tags 2. Label/Tag size customizable 3. We could develop antenna shape on demand</p>									